

Abay Clear Alkyd Varnish

- Resistant to water, alcoholic beverages and alkaline detergents.
- Fast dry and re-coat times.
- Provides sturdy protection against scuffing and rough treatment.
- Resistant to alcohol and other solvents.

A pair of premium quality, fast drying, alkyd varnishes Clear Varnish - Low Luster provides a beautifully durable low lustre finish that simulates a hand-rubbed.

Clear Varnish -High Gloss is excellent for use on floors. Both offer excellent protection against abrasion and scuffing, withstand repeated washings with household cleaners and may be waxed if desired.

For interior wood surfaces such as unfinished or previously finished doors, trim, cabinets, paneling, benches, furniture, tabletops, bars and floors.

- Do not apply when air and surface temperatures are below 40°F (4.4°C)

Colors : Standard Clear High Gloss

Packing : 1 litre & 4 litres

Surface Preparation : Wood, New (Stained or Un-stained): All surfaces must be dry and sanded smooth, and free of dirt, dust, or grit. All nail holes, cracks, and blemishes should be repaired after staining, and filler tinted to Match color of the stain. Open grained woods such as oak or Mahogany that will be subject to water or liquid spills should be filled filler.

Clear Varnish can be applied to bare wood, but applying 1 or 2 coats of a sanding sealer before the finish will give a uniform look with fewer coats.

Technical Data :

Vehicle Type	Clear
Pigment Type	Alkyd
Volume Solids	None
Coverage per Gallon at	43.5%
Recommended Film Thickness	50-60M2
Recommended Film - Wet	2.9 mils
Thickness - Dry	1.3 mils

Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint. Allow final coat to harden 24 hours before subjecting to normal floor traffic.

1 Hour
4 Hours

Dry Time @ 77°F - To Touch
(25°C) @ 50% RH - To Recoat

Dries By	Evaporation, Oxidation
Viscosity	< 56 KU
Flash Point	Combustible
Gloss/ Sheen	Low Lustre
Surface Temperature - Min.	40°F
at Application - Max.	90°F

Thin With	Do Not Thin
Clean Up Thinner	Mineral Spirits
Weight Per Gallon	7.8 lbs
Storage Temperature - Min.	40°F
- Max.	90°F



Manufactured by:

Jelaram Private Limited Company

Gofa Gabriel, Opp. Gaky Honda Car Showroom,
P.O. Box 1027, Addis Ababa Ethiopia (East Africa)

Tel: +251114672867 / 4671240 | Fax: +251114672478

Email: info@abaypaints.com | abaypaints@gmail.com