

DESCRIPTION

- DECOSTUCCO is a prestigious decorative coating with particular effect for interior use.

SPECIFICATION

- DECOSTUCCO is a coating with high strength, good color stability over time and a high level of transpiration.
- Special decorative effects can be obtained using DECOSTUCCO, such as: classic or Antique marble effect, flowered effect, rustic effect and many others, depending on the imagination of the person applying the product.
- After application, the decorated surface remains breathable and washable
- DECOSTUCCO is non-hazardous if used according to its specifications.

APPLICATION

- Ensure that the surface is clean, dry and free from peeling paint or any substance that may compromise adhesion.
- IF there are defects on the surface, these should be smoothed with Sandeco Acrylic Putty
- Prime the surface using the specific decorative primer Sandeco Decoprimer
- DECOSTUCCO should be well mixed before it is applied.
- DECOSTUCCO can be applied using a steel trowel for filling and levelling the undercoat, and putty knives of various different sizes for the topcoat. Apply 3 coats of product (2 base coats + 1 finishing coat).
- Apply one or more coats of the product using the trowel, filling and levelling in order to obtain a smooth and even surface. Allow 5 hours between one application and the next, rubbing down each time with abrasive paper. Apply the finishing coat using the steel putty knife. This operation can be performed by taking only a small amount of the product at a time and applying it with quick, firm strokes of the putty knife. After 5 minutes, the surface can be polished, repeatedly passing the knife back and forth in an oscillatory motion, pressing on the surface. In order to enhance the level of gloss of the finish, it is recommended that the surface. Make sure that both the ambient temperature and the substrate temperature are between +5 °C and +35°C

Drying Time : Dry-to-touch, 2-3 hours / In depth, 24 Hours (recorded at 23°C)

Packaging sizes: 1KG-5KG -10 KG

Coverage : Depending on porosity of surface and environmental conditions, 0,500- 0,700 kg/m² - two coats

Flash Point: Non-flammable.

Storage: 1 year, unopened in cool frost-free conditions

Warning: Keep out of the reach of children. Avoid contact with skin and eyes.