

Abay Polyurethane Varnish Clear

Characteristics:

Polyurethane Varnish is an extremely durable gloss finish that outlasts ordinary varnish 2 to 1. Polyurethane Varnish dries to a hard finish that resists yellowing, abrasion and many household spills. Polyurethane Varnish maintains its new appearance for years.

Vehicle Type: Oil Modified Polyurethane

Finish: Gloss

Recommended Uses: Interior Wood • Floors • Furniture • Exterior Trim • Decks • Trim
Cabinets • Paneling • Exterior Wood

Tinting: Universal colorant may be added per gallon of poly-urethane varnish to shade top-coats.

Thinning: Polyurethane Varnish may be used as its own sealer by mixing mineral spirits to 1 gallon of Polyurethane Varnish. Apply to bare wood and allow to dry. Follow with 1 or 2 coats of Polyurethane Varnish full strength.

Specifications:

DRYING TIME, @ 77° F, 50% RH: Temperature & Humidity Dependent

Touch: 2 Hour

Recoat: 16 hours

Allow 72 hours dry time before heavy Traffic.

Flash Point: 104°

VOC: <475 g/l

Weight Solids: 46 % ± 2%

Volume Solids: 40 % ± 2%

Weight Per Gallon: 4kg

Coverage: 16-18m² per gallon

Application: Apply by brush, roller or low pressure airless spray.

Surface Preparation: Warning! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse affects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator and proper containment and cleanup.

Wood: Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.

Mildew: Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the mildewed area for 10 minutes. Rinse thoroughly with water and allow the surface to dry prior to painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach water solution.

Cleanup Information: Clean spills, spatters, hands and tools immediately after use with mineral spirits. Follow manufacturer's safety recommendations when using mineral Sprits.



Manufactured by:

Jelaram Private Limited Company

Gofa Gabriel, Opp. Gaky Honda Car Showroom,
P.O. Box 1027, Addis Ababa Ethiopia (East Africa)

Tel: +251114672867 / 4671240 | Fax: +251114672478

Email: info@abaypaints.com | abaypaints@gmail.com