

Abay Fine Texture Paint

Description : High quality fine textured finish based on a dispersion of Vam Copolymer resins filled with quartz

Principal Characteristics :

For Interior And Exterior Use • Excellent Color Retention Properties • Moisture Vapor Permeable
Very Good Weather Resistance • Good Resistance Against Wet Cleaning And Scrubbing
Very Good Adhesion And Adhesion Promoting Properties • Can Be Used To Create A Variety Of
Texture Patterns • Almost Odorless • Easy To Apply

Colour and Gloss : See Abay paints shade card

Basic Data At 20 °C

Mass Density : Approx. 1.6g/cm³

Solids Content : Approx. 73% by weight depending on colors

Recommended Dry Film Thickness : Depending upon required finish

Theoretical Spreading Rate : Approx. 9-10m² for 25 kg

Depending on the nature and condition of the substrate and the
Application method employed

Touch Dry After : Approx. 2 hours depending on the thickness

Over Coating Interval : Min. 24 hours, Max. No limitation

Shelf Life (Cool, Dry Place) : 12 months

Flashpoint : Above 65 °C

Available Pack Size : 25 kg

Recommended Substrate Conditions :

- Primed substrates
- Dry and clean primed concrete, cement renders and plaster
- Dirt, dust and other contamination must be removed Previously painted substrates
- Free from defective or poorly adhering paint films
- Wash intact or remaining paint films with a 3% Caustic soda solution
- Not recommended over glossy or solvent borne paint types.

System Specification

Recommended Primers : Abay wall Primer

Recommended Fillers : Gypsum Powder



Manufactured by:

Jelaram Private Limited Company

Gofa Gabriel, Opp. Gaky Honda Car Showroom,
P.O. Box 1027, Addis Ababa Ethiopia (East Africa)

Tel: +251114672867 / 4671240 | Fax: +251114672478

Email: info@abaypaints.com | abaypaints@gmail.com