

# Abay Graffiti Texture Paint

**Description :** High quality weather resistant finishes texture based on PVA Copolymer resins, with fine marble aggregates for superior durability

## **Principal Characteristics :**

For Interior And Exterior Use • High Opacity • Moisture Vapor Permeable • Good Color Retention Properties • Good Adhesion Properties • Can Be Used To Create A Variety Of Texture Patterns Requires No Additional Finish Coats • Easy To Apply • Conforms To Environmental Specifications

**Colour and Gloss :** See Abay Textured Paints Sample Card and Abay classic fan deck for Color Selection - flat

## **Basic Data At 20 °C**

**Mass Density :** Approx 1.8g/Cm<sup>3</sup>

**Solids Content :** Approx. 75% by weight depending on colors

**Recommended Dry Film Thickness :** Depending upon required finish

**Theoretical Spreading Rate :** Approx. 5-6/m<sup>2</sup> for 25kg pail  
Depending on the nature and condition of the substrate and the Application methods employed

**Touch Dry After :** Approx. 4 hours depending on the thickness

**Over Coating Interval :** Min. 12 hours, Max no limitation

**Shelf Life (Cool, Dry Place) :** 12 months

**Flashpoint :** Above 65 °C

**Available Pack Size :** 25 kg

### **Recommended Substrate Conditions :**

- Dry And Clean Primed Concrete, Cement Renders And Plaster
- Dirt, Dust And Other Contamination Must Be Removed Previously Painted Substrates
- Free From Defective Or Poorly Adhering Paint Films
- Wash Intact Or Remaining Paint Films With A 3% Ammonia Solution
- Not Recommended Over Glossy or Solvent Borne Paint Types.

### **System Specification**

**Recommended Primers :** Abay wall Primer

**Recommended Fillers :** Gypsum Powder

**Recommended Finish :** May Be Over-coated With Abay Super Vinyl Matt Emulsion For Additional Protection If Required

### **Instructions For Use**

**Brush And Roller :** 250- 350ml for 25kg

**Recommended Thinner Volume Of Thinner :** Pail



**Manufactured by:**

**Jelaram Private Limited Company**

Gofa Gabriel, Opp. Gaky Honda Car Showroom,  
P.O. Box 1027, Addis Ababa Ethiopia (East Africa)

Tel: +251114672867 / 4671240 | Fax: +251114672478

Email: info@abaypaints.com | abaypaints@gmail.com