

RULOTEX

Product Description: Acrylic emulsion based,water repellent,elastomeric,long lasting exterior textured coating.

- Suitable on exterior mineral surfaces such as concrete, mortar, cement panel and also on interior surfaces for decorative purposes.
- High water vapour permeability, allowing the building to breathe
- Excellent durability and easy to apply
- Resistant to fading,cracking,peeling and UV rays,
- Alkali resistant

Surface Preparation: All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint, and loose surface plaster.Defects and cracks should be repaired with Sandeco Acrylic Putty. Prime new mineral and old painted surfaces with Sandeco Uniprimer with the appropriate color shade of the plaster.RULOTEX can also be used as a primer thinning with %30 of clean water

Application Method :Stir well before use.Apply in a single coat without thinning or in 2 coats by thinning with clean water up to a maximum of 10% by volume using a roller or spray system. Wait for a minimum of 4-6 hours before applying the final coat. Avoid painting in direct sunlight and in hot, humid weather.Lightly dampen very hot surfaces to cool the down before applying the product.Ensure that the air and surface temperatures are above 5°C during the application and 24 hours following the application.

Drying Time :Dry-to-touch, 4-6 hours / In depth,24 Hours (recorded at 23°C)

Packaging sizes: 7,5Ltrs, 15 Ltrs

Consumption : Depending on porosity of surface and environmental conditions smooth surfaces 0.800 - 1.200 kg/m² or 0.500 – 0.800 L /m²

Flash Point: Non-flammable.

Colour : Wide range of colours over tinting system

Storage: 1 year, store unopened at room temperature.

Warning:Keep out of the reach of children.Avoid contact with skin and eyes.

TECHNICAL FEATURES & PHYSICAL CONSTANTS

COLOURS	Available in a range of SANDECO special color card which can be further increased with special colors
DENSITY	1,50±0,02 gr/cm ³
VISCOSITY	Viscous
PH	8,5 – 9,5
VOLUME SOLIDS, %	70± 2
GLOSS GRADE	Matt
FLASH POINT	Water-based.The product is not classified as dangerous. A Material Safety Data Sheet is available on request.
THINNING	Water
DRYING TIME	Dry-to-touch times about 4-6 hours(recorded at 23°C) In depth 24 Hours
COVERAGE	0.800 - 1.200 kg/m ² or 0.500 – 0.800 L /m ²
TEMPERATURE FOR APPLICATION	Depending on porosity of surface and environmental conditions
APPLICATION TOOLS	+ 5 °C - + 35 °C
SIZES & PACKAGING	roller, spray gun
STORAGE AND SHELF LIFE	7,5L – 15L
	1 year, store unopened at room temperature

Deka

BOYA İTHALAT İHRACAT SAN. TİC. LTD. ŞTİ.

Merkez :Atatürk Mahallesi Ekinciöğlü Sokak No:2 Ataşehir-İstanbul/TÜRKİYE Tel:+90(216) 688 33 52(Pbx) Fax: +90(216) 548 20 35

Fabrika:S.S.İstanbul Memmerçiler Küçük San.Sitesi Yapı Koop. 34.Cd.No:3 41490 Gebze-Kocaeli/TÜRKİYE Tel:+90(262) 728 10 88 (Pbx) Fax: +90(262) 728 10 71

www.dekaboya.com.tr e-mail: dekaboya@dekaboya.com.tr

Deka

BOYA İTHALAT İHRACAT SAN. TİC. LTD. ŞTİ.

Merkez : Atatürk Mahallesi Ekinciöğlü Sokak No:2 Ataşehir-İstanbul/TÜRKİYE Tel:+90(216) 688 33 52(Pbx) Fax: +90(216) 548 20 35

Fabrika:S.S.İstanbul Mermerciler Küçük San.Sitesi Yapı Koop. 34.Cd.No:3 41490 Gebze-Kocaeli/TÜRKİYE Tel:+90(262) 728 10 88 (Pbx) Fax: +90(262) 728 10 71

www.dekaboya.com.tr e-mail: dekaboya@dekaboya.com.tr