

DESCRIPTION

- Water-based paint for interiors which features special luminescent sandy reflections.This new finely textured''sand caresses'' decorative finish based on natural fine quartz sands,will highlight any interior wall with a fantastic,harmonic silver effect.

APPLICATION INSTRUCTIONS

- Decoart Silver is a Premium quality,waterborn,decorative finish that reflects sophisticated elegance with super silver reflects.
- The wall gains protection and maintains good breathing characteristics with a depth of colour and look of ageless charm.
- The product has a low odour level,is non flammable and is friendly both to humans and the environment.
- DECOART SILVER can be applied to several surfaces as cement,all kinds of plaster surfaces, as well as wood panels, as long as they are treated with appropriate primers.

APPLICATION TOOLS

- Ensure that the surface is clean,dry and free from peeling paint or any substance that may compromise adhesion.
- Prime the surface using the specific decorative primer Sandeco Decoprimer.
- Use the appropriate brush,dip only tip of the brush into the product and apply unevenly to the surface using short,crossed strokes,flipping and overlapping each time in a random pattern and ensuring an even distribution of the sand on the surface.
- Make sure both the ambient temperature and the substrate temperature are between +5°C and +35°C

Drying Time : Dry-to-touch, 1-2 hours / In depth,24 Hours (recorded at 23°C)

Packaging sizes: 1Lt, 2,5Lt,

Coverage : Depending on porosity of surface and environmental conditions 10-12 lt/m² – one coat

Flash Point: Non-flammable.

Storage: 1 year, unopened in cool frost-free conditions

Warning: Keep out of the reach of children.Avoid contact with skin and eyes.

Deka

BOYA İTHALAT İHRACAT SAN. TİC. LTD. ŞTİ.

Merkez : Atatürk Mahallesi Ekincioğlu sokak No:2 Ataşehir-İstanbul/TÜRKİYE Tel: +90(216) 688 33 52(Pbx) Fax: +90(216) 548 20 35

Fabrika: S.S.İstanbul Memerciler Küçük San.Sitesi Yapı Koop. 34.Cd.No:3 41490 Gebze-Kocaeli/TÜRKİYE Tel: +90(262) 728 10 88 (Pbx) Fax: +90(262) 728 10 71

www.dekaboya.com.tr e-mail: dekaboya@dekaboya.com.tr

TECHNICAL FEATURES & PHYSICAL CONSTANTS

COLOURS	Available in a range of SANDECO special color card which can be further increased with special colors
DENSITY	1,23 ± 0,02 gr/cm ³
VISCOSITY	paste
PH	8,5-9,5
VOLUME SOLIDS, %	53 ± 1
GLOSS GRADE	Semi Matt
FLASH POINT	Water-based.The product is not classified as dangerous. A Material Safety Data Sheet is available on request.
THINNING	Water
DRYING TIME	Dry-to-touch times about 3-4 hours(recorded at 23°C) In depth,24 Hours
COVERAGE	Depending on porosity of surface and environmental conditions 0,250 - 0,350 kg/ m ² - 2 coat
TEMPERATURE FOR APPLICATION	+ 5 °C - + 35 °C
APPLICATION TOOLS	Varnish Brush
SIZES & PACKAGING	1 L, 2,5L
STORAGE AND SHELF LIFE	Store in a dry place Shelf Life = 12 months, unopened.

Deka

BOYA İTHALAT İHRACAT SAN. TİC. LTD. ŞTİ.

Merkez : Atatürk Mahallesi Ekinciöğlü sokak No:2 Ataşehir-İstanbul/TÜRKİYE Tel:+90(216) 688 33 52(Pbx) Fax: +90(216) 548 20 35

Fabrika:S.S.İstanbul Memerciler Küçük San.Sitesi Yapı Koop. 34.Cd.No:3 41490 Gebze-Kocaeli/TÜRKİYE Tel:+90(262) 728 10 88 (Pbx) Fax: +90(262) 728 10 71

www.dekaboya.com.tr e-mail: dekaboya@dekaboya.com.tr