

# Abay Vinyl Matt Emulsion Paint

**Description :** High quality interior/exterior decorative and protective emulsion type Paint based on VAM copolymer resins.

## **Principal Characteristics :**

For Interior And Exterior Use • Good Color Retention Properties • Moisture Vapor Permeable  
Good Weather Resistance • Good Wet And Dry Opacity • Good Adhesion Properties • Good Flow  
And Leveling Properties • Good Wash And Scrub Properties • Almost Odorless • Easy To Apply

**Colour and Gloss :** Abay color chart and Classic chart

**Viscosity :** 115 Ku

## **Basic Data At 20 °C**

**Mass Density :** Approx 1.4g/cm<sup>3</sup>

**Solids Content :** Approx 34% ± 2% by volume depending on colors

**Recommended Dry Film Thickness :** Approx 30μm

**Theoretical Spreading Rate :** Approx. 12 m<sup>2</sup> for 3 coat application

Depending on the nature and condition of the substrate and the  
Application method employed

**Touch Dry After :** Approx. 30 Minutes

**Over Coating Interval :** Min. 2 Hours, Max no limitation

**Shelf Life (Cool, Dry Place) :** 12 months

**Flashpoint :** Above 65 °C

**Available Pack Size :** 1 U.s gallon 3.5 litre

### **Recommended Substrate Conditions :**

- New Primed Substrates
- Dry and Clean Primed Concrete, Cement Render, Plaster, Gypsum and Gypsum Board
- Abrading is Recommended before and Between Applications.
- Dirt, Dust and Other Surface Contamination Must be Removed Prior to Application of finishing coats.
- Previously painted substrates
- Free from defective or poorly adhering paint films
- Wash intact or remaining paint films with a 3% Caustic soda solution
- Not recommended over glossy or solvent borne paint types.

**System Specification:** Bare and repaired areas should be spot primed prior to application

**Recommended Primers :** Abay wall Primer

**Recommended Fillers :** Gypsum Powder

**Recommended Finish :** Applied in three coats of Abay emulsion paint

**Brush And Roller**

**Recommended Thinner :** Sweet Water

**Volume Of Thinner :** Approx. 5 - 10%



**Manufactured by:**

**Jelaram Private Limited Company**

Gofa Gabriel, Opp. Gaky Honda Car Showroom,  
P.O. Box 1027, Addis Ababa Ethiopia (East Africa)

Tel: +251114672867 / 4671240 | Fax: +251114672478

Email: info@abaypaints.com | abaypaints@gmail.com