

Abay Super Gloss Enamel

Description : Quality finish coating based on alkyd resins, producing a durable High gloss finishes for various substrate types.

Principal Characteristics :

For interior and exterior use • Good color retention properties • Good covering and hiding capacity • Particularly suitable for wood and steel • Good weather resistance • Washable and scrub able • Good flow and drying properties • Easy to clean • Easy to apply

Colour and Gloss : See Abay color chart

Basic Data At 20 °C

Mass Density : Approx. 1.15g/cm³

Solids Content : Approx. 50% by volume

Recommended Dry Film Thickness : 35 μ m

Theoretical Spreading Rate : Approx. 14 m²/ltr (57 m²/ USg) for 35 μ m

Depending on the nature and condition of the substrate and the Application method employed

Touch Dry After : Approx. 2 hours

Over Coating Interval : Min. 16 hours, Max no limitation

Shelf Life (Cool, Dry Place) : 24 months

Flashpoint : 39 °C

Available Pack Size : 1 liter & 4 liter

Recommended Substrate Conditions :

- New primed/undercoated substrates
- Dry and clean primed concrete, cement render, plaster, gypsum and gypsum board, timber and metal.
- Abrading is recommended before and between applications
- Dirt, dust and other surface contamination must be removed Previously painted substrates
- Free from defective or poorly adhering paint films
- Wash intact or remaining paint films with a 3% ammonia solution
- Bare and repaired areas should be spot primed prior to application

Brush And Roller : 20-05 (flashpoint 38 °C)

Recommended Thinner Volume Of Thinner : 0 - 5%



Manufactured by:

Jelaram Private Limited Company

Gofa Gabriel, Opp. Gaky Honda Car Showroom,
P.O. Box 1027, Addis Ababa Ethiopia (East Africa)

Tel: +251114672867 / 4671240 | Fax: +251114672478

Email: info@abaypaints.com | abaypaints@gmail.com